



Cap Mushroom Flasher (AC)

CF-25 Cap Flashers are signal flashers designed to be installed into the signal head and flashing beacons systems. These flashers are suitable for flashing tungsten lamp loads. Standard twelve-sided mushroom signal caps provide the housing for both single and dual circuit versions. The circuitry is encapsulated with epoxy to provide a rugged, maintenance-free unit capable of withstanding the environmental requirements at the signal head. A lock ring and gasket are included. Units have an #8 ring terminal attached to twelve inches of hook-up wire for each lead. All units have been tested and are ready to use. Fuse protected units are available. Possible applications include flashing beacons, warning lights, pedestrian and school crossing signals, and four-way stop signals. All Flashers come with two year warranty, made in the United States.

Line Voltage:	95-135VAC	Temperature Range:	-30°F to +165°F
Load Current:	3 Amps	Dimensions:	1- 7/8" Overall Height
Zero Voltage Switching		Flasher Rate:	56 ¼ Flashes/Minute Standard 150 Flashes/Minute Optional

HOOK-UP

Red Wire	AC Line
White Wire	AC Common
Black Wire(s)	Load(s)

STANDARD FLASHER RATE MODELS

<u>Model #</u>	<u>Description</u>
CF-25 -1F	Single Circuit with inline fuse (3A)
CF-25 -2F	Dual Circuit with inline fuse (3A)

Dimmable: Internal Dimmer available as an option – add “Dimmable” to part number. For 150FPM Flasher P/Ns are: CF-2.5X-1, CF-2.5X-1F, CF-2.5X-2, CF-2.5-2F. Specify Cap colors desired from available colors: green, yellow, gloss black.

